Title	Electron Distribution in a Quadrupole Magnetic Field to Drive Magnetic Neutral Loop Discharge Plasma
Author(s)	Osaga, Tsuyoshi; Sakurai, Yohei; Sugawara, Hirotake
Citation	IEEE Transactions on Plasma Science, 39(11), 2546-2547 https://doi.org/10.1109/TPS.2011.2151882
Issue Date	2011-11
Doc URL	http://hdl.handle.net/2115/48517
Rights	© 2011 IEEE. Reprinted, with permission, from Osaga, T., Sakurai, Y., Sugawara, H., Electron Distribution in a Quadrupole Magnetic Field to Drive Magnetic Neutral Loop Discharge Plasma, IEEE Transactions on Plasma Science, Nov. 2011. This material is posted here with permission of the IEEE. Such permission of the IEEE does not in any way imply IEEE endorsement of any of Hokkaido University products or services. Internal or personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution must be obtained from the IEEE by writing to pubs-permissions@ieee.org . By choosing to view this document, you agree to all provisions of the copyright laws protecting it.
Type	article (author version)
File Information	ToPS39-11_2546-2547.pdf

[Instructions for use](#)

Electron Distribution in a Quadrupole Magnetic Field to Drive Magnetic Neutral Loop Discharge Plasma

Tsuyoshi Osaga, *Student Member, IEEE*, Yohei Sakurai, and Hirotake Sugawara

Abstract – We simulated the electron motion in a quadrupole magnetic field that drives a neutral loop discharge (NLD) plasma, using a Monte Carlo method. The structure of the electron distribution in the NLD plasma was observed. Electrons underwent reciprocating motion between reflecting boundaries as they gyrated along magnetic field lines. During this motion, they deviated from the neutral loop and concentrated beside the separatrices of the quadrupole magnetic field.

Index Terms – Electron number density, Monte Carlo method, neutral loop (NL) discharge (NLD) plasma, quadrupole magnetic field, separatrix.

MAGNETIC neutral loop (NL) discharge (NLD) plasma, used for dry etching, is a type of inductively coupled plasma. It can operate at low gas pressures (~ 1 mTorr) and high plasma densities (10^{10} – 10^{11} cm $^{-3}$) [1], [2]. A typical NLD plasma reactor has three coaxial coils surrounding a cylindrical vessel [Fig. 1]. The magnetic field induced by the coil currents is quadrupole, and a ring of zero magnetic field, i.e., the so-called NL, is formed in the vessel. A ring-shaped plasma, i.e., the NLD plasma, is generated along the NL by the electric power from an RF antenna [3]. The radius and position of the NLD plasma are controllable via the coil currents. A dynamic control utilizing this feature for uniform wide-area etching has been proposed [4]. To understand the structure of the NLD plasma, the electron motion in the quadrupole magnetic field was simulated by a Monte Carlo method. In this work, we observed the three-dimensional structure of the electron distribution in the NLD plasma.

The diameter and height of the vessel were both 40 cm. Currents I_1 , I_2 , and I_3 of the top, middle, and bottom coils (60-turn coils) were set at +47.8, –55.75, and +47.8 A, respectively. The radius of the NL formed was 11 cm, and the gradient of the magnetic field was approximately 0.17 mT/cm near the NL. An RF (13.56 MHz) electric field with a sinusoidal waveform was induced by the one-turn RF antenna. Its amplitude at the NL was approximately 4.0 V/cm.

The gas medium was assumed to be CF $_4$ at 5 mTorr.

Fig. 1. Schematic of the NLD plasma reactor and quadrupole magnetic field. X denotes the NL of the zero magnetic field.

The electron collision cross sections of CF $_4$ were taken from [5]. The initial electrons were released in the NL region, which is the region where the magnetic field is weaker than the 0.48-mT strength of the RF-resonant magnetic field and the electric power is deposited into the plasma. The electrons were traced for 200 RF periods and sampled in the last 50 to obtain the time-averaged electron distribution after the initial relaxation process. We assumed a high electron reflectivity of 0.99 at the sidewall, ceiling, and bottom of the vessel, regarding it as the sum of the surface reactions such as electron absorption and emission of the secondary electrons [6].

Fig. 2 shows the electron number density n_e . The high-density region in which n_e is higher than 20% of its peak value is extracted. n_e is low near the separatrices of the quadrupole magnetic field, and electrons concentrate beside the separatrices. Electrons deviate from the separatrices, but further diffusion hardly proceeds. This is explained in the following manner. In the NL region, electrons do not gyrate because the magnetic field is weak. They meander and eventually deviate from the NL region. This leads to low n_e values along the separatrices as well since electrons near the separatrices are from the NL region. Electrons out of the NL region are captured by the magnetic field and gyrate. They move along their guiding magnetic field lines. For the electron reflection at the boundary, electrons undergo reciprocating motions between two boundaries at which the guiding magnetic field lines cross the vessel walls. This reciprocating motion is likely to be maintained at the present low gas pressure. The reciprocating motion along the separatrices is probably aborted in the NL region. In contrast, that

Manuscript received November 30, 2010; accepted April 28, 2011. This work was supported in part by the Japan Society for the Promotion of Science under Grant-in-Aid 22540500 and in part by ULVAC Inc.

The authors are with the Graduate School of Information Science and Technology, Hokkaido University, Sapporo 060-0814, Japan (e-mail: sugawara@ist.hokudai.ac.jp).

Digital Object Identifier 10.1109/TPS.2011.2151882

Published source: IEEE Transactions on Plasma Science 39(11), Pt. 1, 2546-2547 (2011)

Fig. 2. Electron distribution n_e around the separatrixes of the quadrupole magnetic field in the NLD plasma.

beside the separatrixes is maintained. As a result, the peaks of n_e appear beside the separatrixes.

The detailed electron motion in the NLD plasma is described in relation with the NL and separatrixes of the quadrupole magnetic field. While the NL is often considered as the main factor governing the characteristics of the NLD plasma in conventional analyses, the separatrixes also play a key role in determining the structure of the NLD plasma.

REFERENCES

- [1] H. Tsuboi, M. Itoh, M. Tanabe, T. Hayashi, and T. Uchida, "Usefulness of magnetic neutral loop discharge plasma in plasma processing," *Japan. J. Appl. Phys.*, vol. 34, no. 5A, pp. 2476–2481, May 1995.
- [2] H. Tsuboi, T. Hayashi, and T. Uchida, "Observation of induction power dependence on the magnetic neutral loop discharge plasma thermalization phenomena," *Japan. J. Appl. Phys.*, vol. 36, no. 10, pp. 6540–6544, Oct. 1997.
- [3] T. Uchida and S. Hamaguchi, "Magnetic neutral loop discharge (NLD) plasmas for surface processing," *J. Phys. D, Appl. Phys.*, vol. 41, no. 8, pp. 083001-1–083001-21, Apr. 2008.
- [4] H. Sugawara, "Concept of dynamic control of magnetic field for high-throughput and wide-area etching by neutral loop discharge plasma," in *Proc. 63rd Ann. Gaseous Electron. Conf. and 7th Int. Conf. Reactive Plasmas*, Paris, France, 2010.
- [5] M. Kurihara, Z. Lj. Petrović, and T. Makabe, "Transport coefficients and scattering cross-sections for plasma modelling in CF_4 -Ar mixtures: a swarm analysis," *J. Phys. D, Appl. Phys.*, vol. 33, no. 17, pp. 2146–2153, Sep. 2000.
- [6] H. Sugawara, T. Osaga, H. Tsuboi, K. Kuwahara, and S. Ogata, "Numerical simulation of electron transport in electric and magnetic fields for analysis of electron temperature and number density profiles measured in an argon magnetic neutral loop discharge plasma," *Japan. J. Appl. Phys.*, vol. 49, no. 8, pp. 086001-1–086001-5, Aug. 2010.