Title	Topology Optimization Accelerated by Deep Learning
Author(s)	Sasaki, Hidenori; Igarashi, Hajime
Citation	IEEE Transactions on Magnetics, 55(6), 7401305 https://doi.org/10.1109/TMAG.2019.2901906
Issue Date	2019-06
Doc URL	http://hdl.handle.net/2115/74695
Rights	© 2019 IEEE. Personal use of this material is permitted. Permission from IEEE must be obtained for all other uses, in any current or future media, including reprinting/republishing this material for advertising or promotional purposes, creating new collective works, for resale or redistribution to servers or lists, or reuse of any copyrighted component of this work in other works.
Type	article (author version)
File Information	MAGCON-18-11-1747-final.pdf

[Instructions for use](#)

Topology Optimization Accelerated by Deep Learning

Hidehiko Sasaki¹, Hajime Igarashi¹, *IEEE Member*

¹ Graduate School of Information Science and Technology, Hokkaido University, Sapporo, Japan

The computational cost of topology optimization based on stochastic algorithm is shown to be greatly reduced by deep learning. In the learning phase, the cross-sectional image of an IPM motor, represented in RGB, is used to train a convolutional neural network (CNN) to infer the torque properties. In the optimization phase, all the individuals are approximately evaluated by the trained CNN, while finite element analysis for accurate evaluation is performed only for a limited number of individuals. It is numerically shown that computational cost for the topology optimization can be reduced without loss of optimization quality.

Index Terms—Deep learning, Convolutional neural network, Topology optimization, Approximate computing, IPM motor.

I. INTRODUCTION

THE the parameter optimization of electric machines seeks for an optimal solution in the space spanned by the user-defined design variables such as length, nodal position, angle and so on. While this approach has been widely used in industries, it would be difficult to choose the adequate design variables to find a solution with a satisfactory performance. In contrast, the topology optimization does not require setting of the design variables. Moreover, because of the high flexibility in the topology optimization, which allows appearance and disappearance of holes in a design region and free modification of material boundaries, one can find a novel machine structure with excellent performance. It has been shown that the topology optimization based on stochastic algorithm, especially the genetic algorithm (GA), is fairly suitable for the topology optimization of rotating machines [1, 2]. However, this approach requires large computational cost because of a huge number of fitness evaluations using, e.g., the finite element method (FEM).

For reduction of the computational cost in optimization, the approximate computing based on, for example, the response surface method [3] and Kriging method [4] would be effective when the dimension of the design space is less than, say, ten. However, the result of the topology optimization is, in general, an image whose degree of freedoms is far larger than that adequate for the above methods. The artificial neural network (ANN) has been shown effective for the approximate computing for the parameter optimization [5]. It is, however, often difficult to make an adequate choice of the image features to build the input data for ANN. In contrast, when using deep learning (DL) for image processing, image can be directly input to a DL system without the feature design [6].

In this paper, we propose the use of DL for reduction of computing burden in the topology optimization. The authors have shown that DL can accurately infer the torque performance of an interior permanent magnet (IPM) motor

from the cross-sectional image in RGB [7]. In this paper, it is shown that DL is indeed effective for the reduction of computing complexity in the topology optimization. The several ways of the possible use of DL for this purpose are also proposed.

II. TOPOLOGY OPTIMIZATION WITH AID OF DEEP LEARNING

A. Topology Optimization Method

We adopt the topology optimization based on the normalized Gaussian function [1, 2] for the test of the proposed method, which will be briefly described below, while the proposed method can be applied to any topology optimization method in principle. For the numerical examples, we optimize the structure of an IPM motor. To evaluate the performance of an IPM motor, magnetostatic magnetic field is analyzed by FEM.

We introduce the shape function φ defined by

$$\varphi(\mathbf{x}) = \sum_{i=1}^n w_i \tilde{G}(\mathbf{x} - \mathbf{x}_i), \quad (1a)$$

$$\tilde{G}(\mathbf{x} - \mathbf{x}_i) \equiv \frac{G(\mathbf{x} - \mathbf{x}_i)}{\sum_{j=1}^n G(\mathbf{x} - \mathbf{x}_j)} \quad (1b)$$

where G denotes the Gaussian function of the d -th dimension that is centered at $\mathbf{x}_i$, $i = 1, 2, \dots, n$. The Gaussians are uniformly deployed in the design region. Because we consider here two-dimensional magnetic fields, d is set to 2. The material attribute $A_e = \{\text{iron}, \text{air}\}$ of finite element e is determined from

$$\begin{aligned} A_e &= \text{"iron"} \text{ if } \varphi(\mathbf{x}_e) \geq 0, \\ A_e &= \text{"air"} \text{ else,} \end{aligned} \quad (2)$$

where $\mathbf{x}_e$ is the gravitational center of element e . In the topology optimization, the weights w_i , $i = 1, 2, \dots, n$, are determined, using GA in this study, so that the cost function is minimized. The standard deviation included in the Gaussian function is taken larger than the size of the finite elements to avoid convergence to complicated structures.

B. Deep Learning

We adopt DL based on the convolutional neural network (CNN) [6] to perform fast evaluation of the performance of an IPM motor. In this study, the cross-sectional images in RGB ($N = 3$) appeared during the optimization process of an IPM motor are chosen for the input data to CNN. It is also possible to use the weighting coefficients w_i in (1a) as the input data to

Manuscript received April 1, 2015; revised May 15, 2015 and June 1, 2015; accepted July 1, 2015. Date of publication July 10, 2015; date of current version July 31, 2015. (Dates will be inserted by IEEE; “published” is the date the accepted preprint is posted on IEEE Xplore®; “current version” is the date the typeset version is posted on Xplore®). Corresponding author: H. Igarashi (e-mail: igarashi@ssi.ist.hokudai.ac.jp).

Digital Object Identifier (inserted by IEEE).

CNN. However, they are highly problem-dependent. Hence, the CNN trained with w_i is no more valid for other models with a different design region or different n . On the other hand, the image has universality in a sense that many image features are common for different models. For this reason, we use the image as the input to CNN. In our study, CNN is trained to classify different-shaped motor models into categories relevant to the grade of motor properties such as average torque, torque ripple and efficiency.

C. Use of Deep Learning for Optimization

There are two possible ways in the use of DL for acceleration of the topology optimization: on-line and off-line methods. In the former, CNN is trained *during* an optimization process, whereas CNN is trained in the learning phase *prior* to the optimization in the latter case. We will make a discussion about the former elsewhere, while we confine ourselves to the latter in this paper.

The data for training of CNN has to include pairs <image, property> with sufficient diversity. When considering the average torque of an electric motor, for example, we need as uniform distribution of average torque as possible. It would be hard to obtain such data by randomly generation of input images because this would provide only low-torque motors. For this reason, we generate the training data by performing a preliminary topology optimization to maximize average torque which would provide a set of motors with well-distributed torques. Then the trained CNN is used for acceleration of the topology optimization.

Possible ways for the effective use of CNN in the topology optimization are listed in Table 1. In case (i), the trained CNN is used for the optimization problems π_2, π_3 etc. which include cost functions or constraints that are different from those in the preliminary optimization π_1 . In case (ii), CNN is trained with the data obtained by the optimization for model m_1 . Then the trained CNN is used as the approximate computing method in the optimization for different models m_2, m_3 , etc. In the optimization of an IPM motor, the different model would have different magnet position or motor radius, for example. Similarly, in (iii), CNN trained for a set of random seeds in the GA process is used in the optimization phase with different sets of random seeds. In (iv), CNN is firstly trained with the data obtained by the optimization with small population size in GA. Then the trained CNN is used for the optimization with larger population size. In this paper, the feasibility of the proposed method for cases (i) and (ii) is discussed with numerical results. Case (iv) is effective especially for multi-objective problems that need a large computational cost, which is discussed in [8].

Table I Use of deep learning for optimization

	Learning phase	Optimization phase
(i)	problem π_1	problems $\pi_2, \pi_3, \dots$
(ii)	model m_1	models $m_2, m_3, \dots$
(iii)	random seed s_1	random seed $s_2, s_3, \dots$
(iv)	small population size	large population size

D. Reduction in Number of Fitness Evaluation with FEM

In the optimization phase, the fitness evaluation can be

performed only using the trained CNN without FE analysis. However, this might result in an unsuccessful optimization result because of the error in the evaluation with CNN. For this reason, we introduce the probability p of FE analysis depending on the category F of an individual provided by CNN. For the individual belonging to a category with low performance, p is set low because they would not survive in the next generation. In contrast, the additional FE analysis for highly accurate evaluation is made at high p for individuals in categories with high performance. The design of probability distribution function $P(F)$ will be exemplified in the next section.

III. NUMERICAL RESULTS

A. Application to different problem

For a numerical example of (i) in Table I, we consider the topology optimization of the rotor of the IPM motor shown in Fig.1, which include 42 Gaussian bases represented by circles that have the same radius of the standard deviation and are centered at $x_i, i = 1, 2, \dots, 42$. The optimization settings are summarized in Table II. In the learning phase, the training data for CNN is obtained by solving the preliminary optimization problem in which the average torque T_{ave} is maximized:

$$F_1 = \frac{T_{ave}}{T_{ave}^0} \rightarrow \max. \quad (3)$$

where the normalized constant is set as $T_{ave}^0 = 2.1$ Nm, which is the average torque of the original model before optimization. Problem (3) is solved using GA, where we impose the constraint that the iron core is not separated into parts. This constraint is also imposed in the following problems. The torque ripple, $T_{rip} = (T_{max} - T_{min})/T_{ave}$, of the individual generated in the GA process is also evaluated by FEM and stored. By solving (3), we obtain 168,000 samples of <motor image, (T_{ave}, T_{rip}) >. The samples are classified into eight categories shown in Table III with reference to the values of T_{ave} and T_{rip} computed by FEM, and they are provided to CNN. It is found that the classification with respect to T_{rip} is more difficult than that w.r.t. T_{ave} . Hence, we train CNN with 4,000 and 10,000 data for classification of T_{ave} and T_{rip} , respectively, and the remained data that is not used for the training is used for the test of the trained CNN for cross validation.

Fig.1 IPM motor
Circles represent contour of Gaussian-basis functions

The accuracy of the trained CNN is summarized in the confusion matrix shown in Tables IV and V. It is found that samples of 99% and 81% are classified by CNN to the categories within the error range of ± 0.1 compared to those classified by FEM. Since the classification by the trained CNN is not perfect, the additional FE analysis for a subset of individuals would be necessary in the optimization phase.

In the optimization phase, the different problem

$$F_2 = 1.3 \frac{T_{ave}}{T_{ave}^0} - 0.3 \frac{T_{rip}}{T_{rip}^0} \rightarrow \max. \quad (4)$$

is solved with aid of the trained CNN, where $T_{rip}^0 = 0.57$. The five different provability distributions $P_1, P_2, \dots, P_5$ that are functions of F_2 are summarized in Table VI, where case (a) corresponds to the conventional optimization in which all the fitness is evaluated by FEM, whereas no FE analysis is carried out in case (e). In cases (b), (c) and (d), the probability is set higher as the category label becomes higher. The optimization results are shown in Fig.2. It is found that the results (b)-(e) have almost the same values of T_{ave} as that in (a), whereas the result (e) has a relatively large torque ripple. The number of FE analysis in (d) is about 10% of that in (a). Figure 3 shows the numbers of FE analysis per generation in the GA process for the different probabilities. The numbers for P_2, P_3 and P_4 gradually increase with generation because the individuals classified into good categories tends to increase with generation. It is concluded that use of CNN can reduce the computing cost to 10% with little change in the performance of the optimized IPM motor.

Table II Parameters for FE analysis* and GA

Number of genes	42
Number of individuals	800
Number of children	160
Number of generations	100
Current phase angle [degree]	30
Current effective value [A]	4.2425
Number of turns [turn]	35
Residual flux density [T]	1.25

*A customized (in-house) software is used.

Table III Category labels for the data obtained by solving (3)

T_{ave}	(0, 0.45)	(0.45, 0.55)	...	(0.95, 1.05)	(1.05, ∞)
$\hat{T}_{ave}$	0	0.5	...	1.0	1.1
T_{rip}	(0, 0.65)	(0.65, 0.75)	...	(1.15, 1.25)	(1.25, ∞)
$\hat{T}_{rip}$	0	0.7	...	1.2	1.3

$\hat{T}_{ave}$ and $\hat{T}_{rip}$ denote the category labels for T_{ave} and T_{rip} , respectively.

Table IV T_{ave} evaluated by CNN and FEM

		Label by CNN								
		0	0.5	0.6	0.7	0.8	0.9	1	1.1	TOTAL
Label by FEM	0	520	29	4	3	2	1	0	0	559
	0.5	15	452	47	1	0	0	0	0	515
	0.6	0	38	482	49	0	0	0	0	569
	0.7	0	1	38	518	23	0	0	0	580
	0.8	0	0	0	18	390	12	0	0	420
	0.9	0	0	0	3	18	473	15	0	509
	1	0	0	0	0	0	10	396	16	422
	1.1	0	0	0	0	0	0	8	418	426
TOTAL		535	520	571	592	433	496	419	434	4000

B. Application to different model

Here, we consider the application of the trained CNN to different electric-motor model as an example of (ii) in Table I. In the learning phase, CNN is trained with the data obtained by the topology optimization of motor models 1 and 3 shown in

Table V T_{rip} evaluated by CNN and FEM

		Label by CNN								
		0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	TOTAL
Label by FEM	0.6	627	411	53	51	7	28	17	25	1219
	0.7	182	644	186	72	12	14	12	23	1145
	0.8	50	267	589	187	33	38	23	15	1202
	0.9	25	92	223	689	175	96	44	16	1360
	1	12	59	93	259	425	301	72	27	1248
	1.1	10	38	62	105	172	680	240	34	1341
	1.2	24	51	56	55	154	295	520	103	1258
	1.3	18	42	55	58	16	160	291	587	1227
TOTAL		948	1604	1317	1476	994	1612	1219	830	10000

Table VI Probability distributions for problem (4)

Labels of F_2	probabilities [%]				
	P_1	P_2	P_3	P_4	P_5
1.3	100	100	100	100	0
1.2	100	100	50	25	0
1.1	100	100	25	13	0
1	100	50	13	7	0
0.9	100	25	7	4	0
0.8	100	13	4	2	0
0.7	100	7	2	1	0
0	100	0	0	0	0

(a) P_1

(b) P_2

(c) P_3

(d) P_4

(e) P_5

(f) Reference model [9]

Fig.2 Shapes optimized with CNN trained by the different problem. Probability distributions $P_i, i = 1, 2, \dots, 5$, in Table VI are used to solve problem (4).

Fig. 4, where problem (3) is solved. The trained CNN is then used for the optimization of motor model 2 in Fig. 4. The average torque of model 2 is evaluated by the trained CNN. The classification results with respect to T_{ave} provided by FEM and CNN are summarized in the confusion matrix shown in Table VII. The result seems satisfactory; 96% samples are within the range of ± 0.1 . Problem (3) is solved for motor 2 with aid of the trained CNN. The two different probability distributions P'_1 and P'_2 that are functions of F_1 for execution of FE analysis are summarized in Table VIII. The resultant shapes obtained with aid of the trained CNN are shown in Fig.5. There are no significant differences both in the rotor shapes and torque performances. The total number of FE analysis in (b) is about 33% of the that in (a) which corresponds to the topology optimization without DL.

Fig.3 Change in number of FE analysis

Table VII T_{ave} evaluated by CNN and FEM for model 2 in Fig.4

		Label by CNN								TOTAL
		0	0.5	0.6	0.7	0.8	0.9	1	1.1	
Label by FEM	0	397	76	24	21	16	10	4	0	548
	0.5	29	360	62	1	0	0	0	0	452
	0.6	7	83	315	74	1	0	0	0	480
	0.7	10	1	103	335	76	0	0	0	525
	0.8	17	0	1	65	286	59	0	0	428
	0.9	10	0	0	1	96	350	46	0	503
	1	0	0	0	0	2	148	374	10	534
	1.1	0	0	0	0	0	0	269	261	530
TOTAL		470	520	505	497	477	567	693	271	4000

Fig.4 IPM motors with different position of permanent magnet

Table VIII Probability distributions for problem in III.B

Labels of F_1	probabilities [%]	
	P'_1	P'_2
1.1	100	100
1.0	100	25
0.9	100	13
0.8	100	7
0.7	100	4
0.6	100	1
0.5	100	1
0	100	0

Fig.5 Shapes optimized with CNN trained by different model. Probability distributions P'_1 and P'_2 in Table VIII are used to solve problem (3).

IV. CONCLUSIONS

In this paper, a method based on DL to accelerate the topology optimization using a stochastic optimization method has been proposed. In this method, the individuals in the GA process of the topology optimization are evaluated by the CNN prepared in the learning phase prior to the optimization. The FE analysis for the evaluation of the individuals is performed in accordance with a probability that depends on the categories provided by CNN. It has been shown that the average torque and torque ripple are accurately classified by the trained CNN. The optimization results obtained with aid of the CNN trained for a different problem as well as different models have little differences in the shape and performance compared with those obtained by the conventional method. The computing costs are reduced to about 10% and 33%, respectively. We plan to develop the method to extract design features necessary for good motor performances from the trained CNN in future. Moreover we will study the data size and training method to realize the CNN which accurately infers the performances of motors with different magnet shape, location and magnetization as well as different number of poles and teeth.

REFERENCES

- [1] T. Sato, K. Watanabe, H. Igarashi, Multimaterial Topology Optimization of Electric Machines Based on Normalized Gaussian Network, *IEEE Trans. Magn.*, vol. 51, no. 3, 7202604, 2015.
- [2] S. Sato, T. Sato, H. Igarashi, Topology Optimization of Synchronous Reluctance Motor Using Normalized Gaussian Network, *IEEE Trans. Magn.*, vol. 51, Issue 3, 8200904, 2015
- [3] R. H. Myers, D. C. Montgomery, C. M. Anderson-Cook, Response surface methodology: Process and product optimization using designed experiments, 3rd Ed., Wiley, 2009
- [4] L. Lebensztajn, C.A.R. Marretto, M.C. Costa and J.-L. Coulomb, Kriging: a useful tool for electromagnetic device optimization, *IEEE Trans. Magn.*, vol. 40, no. 2, pp. 1196-1199, 2004
- [5] S. Shimokawa, et al., Fast 3-D Optimization of Magnetic Cores for Loss and Volume Reduction, *IEEE Trans. Magn.*, vol. 54, no. 11, 8400904, 2018
- [6] Y. LeCun, Y. Bengio, G. Hinton, Deep Learning, *Nature*, vol.521, 436-444, 2015.
- [7] H. Sasaki, H. Igarashi, Topology Optimization of IPM Motor with Aid of Deep Learning, presented at ISEM2017, to be published in *Int. J. Appl. Electromagnetics and Mech.*, DOI: 10.3233/JAE-171164.
- [8] S. Doi, H. Sasaki, H. Igarashi, Multi-objective Topology Optimization of Rotating Machines Using Deep Learning, presented at CEFC2018, to be published in *IEEE Trans. Magn.*
- [9] Technical report of the institute of electrical engineering of Japan, industry application society, no.776, 2000.