

HOKKAIDO UNIVERSITY

Title	Experimental observation of pulsating instability under acoustic field in downward-propagating flames at large Lewis number
Author(s)	Yoon, Sung Hwan; Hu, Longhua; Fujita, Osamu
Citation	Combustion and Flame, 188, 1-4 https://doi.org/10.1016/j.combustflame.2017.09.026
Issue Date	2018-02
Doc URL	http://hdl.handle.net/2115/76640
Rights	© 2018. This manuscript version is made available under the CC-BY-NC-ND 4.0 license http://creativecommons.org/licenses/by-nc-nd/4.0/
Rights(URL)	http://creativecommons.org/licenses/by-nc-nd/4.0/
Туре	article (author version)
Additional Information	There are other files related to this item in HUSCAP. Check the above URL.
File Information	Supplementary materials.pdf



1. Detailed Experimental Methods



Fig. 1 Schematic representation of the experimental apparatus.

The experimental apparatus is schematically outlined in Fig. 1. The propagation tube (transparent acrylic tube, 50 mm inner diameter, 711 mm length) was fixed vertically and charged with the tested gas at atmospheric pressure. A point ignition system using a spark plug was located near the upper end of the tube. When the spark igniter was activated, the top lid was simultaneously opened by an automatic opening system of the top lid of the tube powered by an electromagnet and a mechanical spring. The time-dependent behaviors of the downward-propagating flame were recorded by two high-speed cameras. the high-speed cameras One of (FASTCAM Mini UX100 recording at 2000 fps) captured images from side view of the tube. Another high-speed camera (nac HSV-500C3 recording at 500 fps) captured bottom view of the propagating flame in inclined angle as shown in Fig.1. Temporal pressure variation was measured with a PCB Piezotronics 106B52 dynamic pressure sensor located at the bottom end of the tube at a sampling rate of 10 kHz.

In this study, the premix gas composed of propane, oxygen and nitrogen were set at atmospheric pressure in the tube as shown in Table 1. We selected equivalence ratios of 0.8 and 1.2 to change Le. To vary laminar burning velocities with the fixed equivalence ratio, we changed dilution ratio, D = $\frac{O_2}{O_2+N_2 \text{ or } CO_2}$. The flame properties (e.g., laminar burning velocities, S_L , speed of sound, с. and adiabatic flame temperatures, $T_{\rm b}$) were calculated using CHEMKIN (Premix code/ USC II) [1]. Zel'dovich number could be The calculated by $\beta = E(T_{\rm b} - T_{\rm u})/(RT_{\rm b}^2)$. Here, E is the activation energy, R is the gas constant, and the subscripts u and b identify unburned and burned mixtures, respectively. Peters and Williams [2]

Mix.	C_3H_8	O_2	N_2	Φ	$S_{\rm L}$ (cm/s	Т _ь (К)	βM	Le	β (Le-1)	Regime
1	0.027	0.169	0.804	0.8	17.5	1833	0.0058	1.86	9.82	Ι
2	0.028	0.175	0.797		20.0	1881	0.0065		9.72	Ι
3	0.029	0.182	0.789		22.5	1927	0.0074		9.76	Ι
4	0.030	0.188	0.782		25.0	1969	0.0083		9.84	Π
5	0.031	0.194	0.775		27.5	2009	0.0092		9.85	IV
6	0.032	0.200	0.768		30.0	2046	0.0101		9.78	IV
7	0.033	0.206	0.762		32.5	2082	0.0110		9.84	IV
8	0.034	0.211	0.755		35.0	2114	0.0120		9.89	III-2
9	0.035	0.217	0.749		37.5	2145	0.0129		9.92	III-2
10	0.035	0.222	0.743		40.0	2175	0.0139		10.03	V
11	0.036	0.227	0.737		42.5	2203	0.0151		10.17	v
12	0.033	0.135	0.832	1.2	7.5	1705	0.0038	1.04	0.73	II
13	0.034	0.142	0.823		10.0	1761	0.0046		0.63	II
14	0.036	0.149	0.816		12.5	1812	0.0053		0.56	III-1
15	0.037	0.155	0.808		15.0	1859	0.0060		0.52	III-1
16	0.039	0.161	0.801		17.5	1905	0.0066		0.48	IV
17	0.040	0.166	0.794		20.0	1948	0.0073		0.45	IV
18	0.041	0.172	0.787		22.5	1990	0.0079		0.41	IV
19	0.042	0.177	0.781		25.0	2030	0.0086		0.40	V
20	0.046	0.192	0.761		32.5	2139	0.0108		0.36	V
21	0.051	0.212	0.737		42.5	2268	0.0138		0.32	V

Table 1 Detailed gas properties for the tested gas.

defined the activation energy as $\frac{E}{R} = -\frac{d2[\ln(\rho_u S_L)]}{d(1/T_b)}$ where ρ is density of gas

mixture. The Mach number, M, which appears in table 1, is defined as $M = S_L/c$. Lewis number was given by the ratio of the thermal diffusivity of mixture to the mass diffusivity of deficient gas species, $Le = \alpha/D_{\text{dif}}$. We selected two different Le for $Le \approx 1.85$ from Mix. 1–11 and $Le \approx 1.04$ from Mix. 12–21. To observe pulsating instability, we conducted experiments with various reduced *Le*, $\beta(Le-1)$, which can be varied by different equivalence ratios and laminar burning velocities.

Reference

[1] Z. Qin, V. Lissianski, H. Yang, W. C.Gardiner, S. G., Davis, H. Wang, Proc.Combust. Inst. 28 (2000) 1663-1669.

[2] N. Peters, F. A. Williams, Combust. Flame 68 (1987) 185-207.