



Title	Development of High Performance Manganese-based Cathode Materials for Li-ion Batteries [an abstract of dissertation and a summary of dissertation review]
Author(s)	韓, 成功
Degree Grantor	北海道大学
Degree Name	博士(工学)
Dissertation Number	甲第12755号
Issue Date	2017-03-23
Doc URL	https://hdl.handle.net/2115/65426
Rights(URL)	https://creativecommons.org/licenses/by-nc-sa/2.1/jp/
Type	doctoral thesis
File Information	Han_ChengGong_abstract.pdf, 論文内容の要旨



学 位 論 文 内 容 の 要 旨

博士の専攻分野の名称 博士（工学） 氏名 韓 成 功

学 位 論 文 題 名

Development of High Performance Manganese-based Cathode Materials for Li-ion Batteries

(Li イオン電池のための高性能 Mn 系カソード用材料の開発)

Rechargeable *Li*-ion batteries are considered as one of the most effective devices for storing the renewable energies without air pollution. The urgent demands from the application markets, e.g. smart phones, laptops, electric vehicles, hybrid electric vehicles, require the development of high power/energy rechargeable *Li*-ion batteries, which are mainly determined by the relatively low capacity of cathode materials. *Mn*-based oxide cathode material, spinel LiMn_2O_4 , is paid more attentions due to its low cost, no toxicity, environmental friendliness, relatively high energy density compared with the commercialized LiCoO_2 . However, its further application is restricted by the serious capacity fading in cycling process, arising from the dissolution of manganese, Jahn-Teller distortion, and structural instability. In this work, three technologies, synthetic technology, doping technology, and surface modification technology, are proposed to overcome and alleviate the above problems. Solution combustion synthesis is employed as synthetic technology; *Bi* and *La* co-doping is chosen as doping technology; modifying a Mn^{4+} -rich phase, and a Li_2CuO_2 - Li_2NiO_2 solid solution on the surface of LiMn_2O_4 particles is served as surface modification technology. In addition, another *Mn*-based oxide cathode material, *Li*-rich layered $x\text{Li}_2\text{MnO}_3$ -(1-*x*) $\text{LiNi}_{1/3}\text{Co}_{1/3}\text{Mn}_{1/3}\text{O}_2$ is also introduced and prepared due to its high capacity with the possible application in the future. This thesis includes 6 chapters, in which the first and last chapters are general introduction and general conclusion, respectively.

Chapter 2 shows the solution combustion synthesis of LiMn_2O_4 powders. Mixed fuels of glycine and sucrose with different molar ratios were used to produce the LiMn_2O_4 powders with sizes of 100 – 200 nm. The effects of different molar ratios of glycine to fuel on the phase structure, morphologies, yields, and electrochemical performance of final LiMn_2O_4 were investigated in detail. The presence of sucrose in the fuels was in favor of producing nanosized LiMn_2O_4 particles, improving yields, alleviating the explosive combustion reaction, and resulting in the nondecreasing electrochemical performance.

Chapter 3 presents doping technology for obtaining the high electrochemical performance of spinel LiMn_2O_4 . *Bi* and *La* as doping elements were employed to prepare $\text{LiBi}_x\text{La}_x\text{Mn}_{2-2x}\text{O}_4$ materials. A substitution of *Mn* by *Bi* and *La* resulted in the enlarged lattice parameters, and more stable structure, which facilitated the fast diffusion of *Li*-ions, and cycling stability, respectively. A remarkably improved electrochemical performance of LiMn_2O_4 was observed due to the synergistic effect of *Bi* and *La* in spinel structure.

Chapter 4 displays surface modification technology for improving the electrochemical performance of spinel LiMn_2O_4 . Two kinds of materials, a Mn^{4+} -rich phase, and a Li_2CuO_2 - Li_2NiO_2 solid solution, were chosen as the surface modified materials. In this chapter, the modified amounts played a critical role on the phase structure, morphologies and electrochemical performance. The presence of a Mn^{4+} -rich phase alleviated the dissolution of manganese in the electrolyte, thus improving the cycling performance and rate capability relative to the bare LiMn_2O_4 . In addition, when using a Li_2CuO_2 - Li_2NiO_2 solid solution, the modified layer on the surface of LiMn_2O_4 particles, featuring a $\text{LiNi}_z\text{Mn}_{2-z}\text{O}_4$ -like

phase as well as a Li_2CuO_2 - Li_2NiO_2 solid solution, played a key role in alleviating the dissolution of manganese, thus enhancing the cycling performance and rate capability.

In Chapter 5, *Li*-rich layered xLi_2MnO_3 -(1- x) $LiNi_{1/3}Co_{1/3}Mn_{1/3}O_2$ oxides were prepared by solution combustion synthesis using the mixed fuels of glycine and sucrose. Phase structure, morphologies, electrochemical performance were determined by x values. Different x led to the different electrochemical performances. For comparison, $0.4Li_2MnO_3$ - $0.6 LiNi_{1/3}Co_{1/3}Mn_{1/3}O_2$ oxide was also prepared by using glycine as the only fuel. Using different fuels led to the different phase structure, morphologies, and electrochemical performance.

The final goals for obtaining high electrochemical performance of *Mn*-based cathode oxides were reached.