



HOKKAIDO UNIVERSITY

Title	Ohmic Heating for Milk Pasteurization : Effect of Electric Current on Nonthermal Injury to <i>Streptococcus thermophilus</i>
Author(s)	Sun, Huixian; Kawamura, Shuso; Himoto, Jun-ichi et al.
Description	Written for presentation at the 2006 ASABE Annual International Meeting Sponsored by ASABE
Citation	ASABE meeting paper, No. 066025 https://doi.org/10.13031/2013.21471
Issue Date	2006
Doc URL	https://hdl.handle.net/2115/71270
Rights	Technical presentations are not subject to the formal peer review process by ASABE editorial committees; therefore, they are not to be presented as refereed publications. Citation of this work should state that it is from an ASABE meeting paper. EXAMPLE: Author's Last Name, Initials. 2006. Title of Presentation. ASABE Paper No. 06xxxx. St. Joseph, Mich.: ASABE.
Type	journal article
File Information	Ka2006-2 Ohmic Heating by Sun finishe.pdf





American Society of
Agricultural and Biological Engineers

An ASABE Meeting Presentation

Paper Number: 066025

Ohmic Heating for Milk Pasteurization: Effect of Electric Current on Nonthermal Injury to *Streptococcus thermophilus*

Huixian Sun, Graduate Student

Agricultural and Food Process Engineering Lab. Hokkaido University, Sapporo 060-8589,
Japan, son@bpe.agr.hokudai.ac.jp

Shuso Kawamura, Associate Professor

Agricultural and Food Process Engineering Lab. Hokkaido University, Sapporo 060-8589,
Japan, shuso@bpe.agr.hokudai.ac.jp

Jun-ichi Himoto, Assistant Professor

Agricultural and Food Process Engineering Lab. Hokkaido University, Sapporo 060-8589,
Japan, himo@bpe.agr.hokudai.ac.jp

Tatsuhiko Wada, Professor

Agricultural and Food Process Engineering Lab. Hokkaido University, Sapporo 060-8589,
Japan, wada@bpe.agr.hokudai.ac.jp

**Written for presentation at the
2006 ASABE Annual International Meeting
Sponsored by ASABE
Portland Convention Center
Portland, Oregon
9 - 12 July 2006**

The authors are solely responsible for the content of this technical presentation. The technical presentation does not necessarily reflect the official position of the American Society of Agricultural and Biological Engineers (ASABE), and its printing and distribution does not constitute an endorsement of views which may be expressed. Technical presentations are not subject to the formal peer review process by ASABE editorial committees; therefore, they are not to be presented as refereed publications. Citation of this work should state that it is from an ASABE meeting paper. EXAMPLE: Author's Last Name, Initials. 2006. Title of Presentation. ASABE Paper No. 06xxxx. St. Joseph, Mich.: ASABE. For information about securing permission to reprint or reproduce a technical presentation, please contact ASABE at rutter@asabe.org or 269-429-0300 (2950 Niles Road, St. Joseph, MI 49085-9659 USA).

Abstract. *Experiments on milk pasteurization were conducted with cells of Streptococcus thermophilus 21072 to confirm the lethal effect of electric current using combination treatment (sublethal ohmic and conventional heating treatment) and control treatment (conventional heating treatment only). Bacteria counts and calculated decimal reduction times (D value) of combination treatment indicated that combination treatment had significantly higher lethality than that of control treatment under the condition of the same temperature histories ($p < 0.05$). However, no pasteurizing effect of the electric current on bacteria cells was observed during the sublethal ohmic treatment. The results suggested that sublethal ohmic treatment decreased the heat resistance of bacteria probably due to nonthermal injury of bacteria caused by the electric current.*

Keywords. milk, pasteurization, ohmic heating, electric current, nonthermal injur

Introduction

Food sterilization is one of the most important processes in food industries. Novel low-energy or efficient methods of sterilization continue to attract interest of food engineers. Anderson and Finklestein (1919) initially examined milk sterilization with electric fields. In recent years, ohmic heating and high-voltage pulsed electric field processes have been studied as alternative methods to conventional heating sterilization (Castro et al., 2004; Cho et al., 1999; Gilliland and Speck, 1967a, 1967b; Imai et al., 1995; Pareilleux and Sicard, 1970; Tsong, 1991).

Although the effect of electricity on microorganisms has been studied, the thermal (ohmic heating) effect of electricity has never been satisfactorily explained. Microbial inactivation during low-voltage electrical treatment has been attributed primarily to heating since the interaction between electric fields and microorganisms has not been elucidated.

Palaniappan et al. (1992) reported that there was no difference between the effects of ohmic heating and conventional heating under the condition of identical thermal histories on the death kinetics of yeast cells. They found, however, that mild electrical pretreatment of *Escherichia coli* decreased the subsequent inactivation requirement in certain cases. In other studies, an inactivation effect on bacteria at sublethal temperatures was observed using an alternating low-voltage current (Pareilleux and Sicard, 1970; Shimada and Shimahara, 1985). Cho et al. (1999) found that the kinetics of inactivation of *Bacillus subtilis* spores can be accelerated by ohmic treatment. Recent studies suggest that mild electroporation might occur during ohmic heating and high-voltage electrical treatment (Imai et al., 1995; Kulshrestha et al., 1999; Yoon et al., 2002). Yoon et al. (2002) reported that leakage of intracellular constituents of *S. cerevisiae* is greater under the condition of ohmic heating than under the condition of conventional heating in boiling water. We reported that death rates of viable aerobes and *Streptococcus thermophilus* 2646 resulting from ohmic heating indicated that ohmic heating had significantly higher lethality than that of conventional heating under the condition of the same temperature histories ($p < 0.05$) (unpublished data).

There is little information on the effect of the electrical current during ohmic heating on microbes. Accordingly, the aim of this study was to determine the effect of electric current on pasteurization of microorganisms during ohmic heating.

Materials and methods

Bacterial strains and materials

Streptococcus thermophilus 21072 was cultivated in 12.6% (in weight) skim milk and the culture was incubated at 37°C for 48 h. The concentrated culture was suspended in commercial whole milk (purchased at a supermarket in Sapporo, Hokkaido, Japan) to acquire ca. 10^7 cells/mL.

Experimental setup

The ohmic heating setup consisted of a wide-band function generator (NF Electronic Instruments, FG-143, Japan), a precision power amplifier (NF Electronic Instruments, 4510, Japan), two digital multimeters (Iwatsu SC-303A GP-IB unit, Voac7411, Japan), a data logger (Eto Denki co. Thermodac model 5020A, Japan), a computer, and a heating unit (Fig.1). The heating unit consists of titanium (Ti) electrodes for contact with the sample and a thermocouple (k-type) inserted in an acrylic box. The distance between the two electrodes was 30 mm, and the size of each electrode contacting with the sample was 101×85 mm. Time and temperature data

were collected with a data logger linked to a computer, and the voltage and current data were collected with two digital multimeters linked to the same computer. As control, conventional heating was performed in a water bath with an aluminum vessel of 300 mL in capacity.




Figure1. Schematic diagram of the experimental setup.

Combination treatment and control treatment

The death rates of *Streptococcus thermophilus* 21072 cultured in milk were evaluated during combination treatment (sublethal ohmic and conventional heating treatment) and control treatment (conventional heating treatment). Figure 2 shows the procedure used for combination treatment. In the case of sublethal ohmic treatment, a 250-ml milk sample was subjected to an alternating current of 7 A with a frequency of 20 kHz for 1 min until the temperature increased from 10°C to 42°C and then immediately cooled to 10°C in a cold water bath for 5 min. Changes in voltage and current during sublethal ohmic heating are shown in Figure 3. Heating and cooling histories during sublethal ohmic treatment are shown in Figure 4. To perform long sublethal ohmic treatment, the operations of ohmic heating and cooling were repeated 12 times. After the 12th sublethal treatment, the sample was immediately subjected to conventional heating for 5 min until the temperature increased to 70°C and was held at 70°C for 6 min. For control treatment, a 250-ml sample was heated for 5 min from 10°C to 70°C and was held at 70°C for 6 min. Conventional heating in the combination treatment performed by exactly the same procedure as that of control treatment in order to match the time-temperature histories within $\pm 0.5^\circ\text{C}$. Figure 5 shows a comparison of thermal histories during conventional heating for combination and control treatments.




Figure 2. Procedure for combination treatment of sublethal ohmic treatment and conventional heating treatment.




Figure 3. Voltage and current histories during sublethal ohmic heating.




Figure 4. Heating and cooling history during sublethal ohmic heating.




Figure 5. Comparison of temperature histories during conventional heating for combination and control treatments.

Microbiological analysis

The microbiological medium used in this study was purchased from Merck (Darmstadt, Germany). *Streptococcus thermophilus* 21072 counts were determined by calculating the colonies from M17 medium containing a diluted sample (1 mL) that had been cultured at 37°C for 72 h. Five independent replications of each experiment were conducted. Decimal reduction times (D value: time in minutes required for log-cycle reduction in bacterial population) were calculated from the slope of the regression line fitted to the survival plots.

Statistics

Statistical analysis was carried out using software (MS-Excel 2000, Microsoft). All data were subjected to variance analysis and a least significant difference test to determine significant differences ($P < 0.05$) between treatments.

Results and discussion

In the holding phase in all experiments, standard deviations of temperature difference between the center temperature of the sample and set temperature were 0.19-0.21 °C (combination treatment) and 0.11-0.18 °C (control treatment). Therefore, it is clear that the temperature was appropriately controlled and that the experimental conditions of the two treatments were identical.

Representative survival counts for *Streptococcus thermophilus* 21072 during combination treatment and control treatment are presented in Figure 6. The D values determined from survivor curves are shown in Figure 7. No difference in survival counts was observed between the initial samples and the samples subjected to sublethal ohmic treatment (Fig. 6). However, significant differences in survival counts and D values were found between combination treatment and control treatment during holding time. These results suggested that there was a synergistic effect of sublethal ohmic and conventional heating treatment on bacteria cell death. It is possible that sublethal ohmic treatment decreased heat resistance of bacteria, since no cell death was observed during sublethal ohmic treatment. The mechanism by which an electric current causes bacteria to be weak in heat resistance remains unclear. However, the results of this study suggest that ohmic heating enhances nonthermal injury caused by electric current on bacteria. Ohmic heating is therefore an effective method of pasteurization because of the combination of a nonthermal effect by electric current and lethal thermal effect by Joule heat generation.




Figure 6. Comparison of survival of *Streptococcus thermophilus* subjected to control treatment and combination treatment.

*: No growth.

Initial: No treatment.

Before conventional heating: After being treated with sublethal ohmic treatment of combination treatment.

Holding time 0: The time when the samples were heated to the set temperature (70°C).




Figure 7. Regression line of heating time and *Streptococcus thermophilus* counts.

Palaniappan et al. (1992) reported that there was no difference between the effects of ohmic and conventional heat treatments under the condition of identical thermal histories on the death kinetics of yeast cells at currents ranging from 0.5 to 1.0 A of 60 Hz. Moreover, mild electrical pretreatment of *Escherichia coli* decreased the subsequent inactivation requirement only in a few cases. The current and frequency used in this study were 7 A and 20 kHz, respectively, which were higher than those used in the experiments of Palaniappan et al. (1992). Lee and Yoon (2002) reported that intracellular protein leakage is induced by ohmic heating and that the amount of exuded protein increased significantly as the electric field was changed from 10 to 20 V/cm with a frequency of 60 Hz. In similar, more proteins are exuded when higher frequencies (60 kHz) are applied. Accordingly, an additional lethal effect of ohmic heating is possible due to the higher current and frequency. Therefore, we speculate that an effect of ohmic heating on pasteurization can be obtained with appropriate current strength and frequency. Additional studies are needed to prove this hypothesis and verify the nonthermal effect of electricity on bacteria. Further investigation is also needed to elucidate how ohmic heating enhances killing of bacteria.

Conclusions

The results of our comparative study on lethal effects on *Streptococcus thermophilus* 21072 show that there was a significant difference between the combination treatment and control treatment on death rates. An electric current could not generate a lethal effect on bacteria but caused a decrease in heat resistance of bacteria due to nonthermal injury. Nonthermal injury caused by an electric current had a significant effect on killing of bacteria during thermal lethal treatment. The results suggest that the mechanism by ohmic heating kills bacteria is probably the combination of the nonthermal effect of the electric current and the lethal thermal effect.

Acknowledgements

The authors appreciate bacteria supply from Laboratory of Applied Microbiology, Graduate School of Agricultural Science, Hokkaido University. The authors are also grateful for the advice from Emeritus Professor Kazuhiko Itoh and support in the ohmic heating setup from staff of Frontier Engineering Co.

References

- Anderson, A.K., and R. Finklestein. 1919. A study of the electro-pure process of treating milk. *J. Dairy Sci.* 2: 374-406.
- Castro, I., B. Macedo, JA. Teixeira, and AA. Vicente. 2004. The effect of electric field on important food processing enzymes: Comparison of inactivation kinetics under conventional and ohmic heating. *J. Food Sci* 69 (9): 696-701.
- Cho, H.-Y., A.E. Yousef, and S.K. Sastry. 1999. Kinetics of Inactivation of *Bacillus subtilis* Spores by Continuous or Intermittent Ohmic and Conventional Heating. *Biotech. Bioeng.* 62(3): 368-372
- Gilliland, S.E., and M. L. Speck. 1967a. Inhibition of microorganisms by electrohydraulic shock. *Appl. Microbiol.* 13: 1031-1037.
- Gilliland, S. E., and M. L. Speck. 1967b. Mechanism of bactericidal action produced by electrohydraulic shock. *Appl. Microbiol.* 15: 1038-1044.
- Imai, T., K. Uemura, N. Ishida, S. Yoshizaki, and A. Noguchi. 1995. Ohmic heating of Japanese White Radish *Rhaphanus sativus* L. *Int. J. Food Sci. Technol.* 30: 461-472.
- Ines Birlouez-Aragon, N., M. Icolas, A. Meyais, N. Marchond, J. Grenier, and D. Calvo. 1998. A rapid fluorimetric method to estimate the heat treatment of liquid milk. *Int. Dairy J.* 8: 771-777
- Kulshrestha, S.A., and S.K. Sastry. 1999. Low-frequency dielectric changes in vegetable tissue from ohmic heating. In the 1999 Annual IFT Meeting, Chicago, IL, Abstract No. 79 B-3.
- Palaniappan, S., S. K. Sastry, and E. R. Richter. 1992. Effects of electroconductive heat treatment and electrical pretreatment on thermal death kinetics of selected microorganisms. *Biotech. Bioeng.* 39: 225-232.
- Pareilleux, A., and N. Sicard. 1970. Lethal effects of electric current on *Escherichia coli*. *Appl. Microbiol.* 19: 421-424.
- Shimada, K., and K. Shimahara. 1985. Changes in surface charge, respiratory rate and stainability with crystal violet of resting *Escherichia coli* B cells anaerobically exposed to an alternating current. *Agric. Biol. Chem.* 49: 405-411.
- Tsong, T. Y. 1991. Electroporation of cell membranes. *Biophys. J.* 60: 297-306.
- Yoon, S.W., C. Y. J. Lee, K.M. Kim, and C.H. Lee. 2002. Leakage of cellular material from *Saccharomyces cerevisiae* by ohmic heating. *J. Microbiol. Biotechnol.* 12(2): 183-188.