



HOKKAIDO UNIVERSITY

Title	Near-infrared Spectroscopy for On-line Real-time Monitoring of Milk Quality : Spectrum Analysis by Principal Component Analysis
Author(s)	Kawasaki, M.; Kawamura, S.; Nakatsuji, H. et al.
Description	Written for presentation at the 2006 ASABE Annual International Meeting Sponsored by ASABE
Citation	ASABE meeting pape, No. 063049
Issue Date	2006
Doc URL	https://hdl.handle.net/2115/71272
Rights	Technical presentations are not subject to the formal peer review process by ASABE editorial committees; therefore, they are not to be presented as refereed publications. Citation of this work should state that it is from an ASABE meeting paper. EXAMPLE: Author's Last Name, Initials. 2006. Title of Presentation. ASABE Paper No. 06xxxx. St. Joseph, Mich.: ASABE.
Type	journal article
File Information	Ka2006-4 Full Pepar2006ASABE(063049).pdf





American Society of
Agricultural and Biological Engineers

An ASABE Meeting Presentation

Paper Number: 063049

Near-infrared Spectroscopy for On-line Real-time Monitoring of Milk Quality: Spectrum Analysis by Principal Component Analysis

Masataka Kawasaki, Graduate Student

Agricultural and Food Process Engineering Lab. Hokkaido University, Sapporo 060-8589,
Japan, kawasaki@bpe.agr.hokudai.ac.jp

Shuso Kawamura, Associate Professor

Agricultural and Food Process Engineering Lab. Hokkaido University, Sapporo 060-8589,
Japan, shuso@bpe.agr.hokudai.ac.jp

Hiroki Nakatsuji, Associate Professor

Animal Production Systems Lab. Hokkaido University, Sapporo 060-8589, Japan
nakahiro@anim.agr.hokudai.ac.jp

Motoyasu Natsuga, Associate Professor

Agricultural Ecology and Engineering, Yamagata University, Tsuruoka 997-8555, Japan,
toko@tds1.tr.yamagata-u.ac.jp

**Written for presentation at the
2006 ASABE Annual International Meeting
Sponsored by ASABE
Portland Convention Center
Portland, Oregon
9 - 12 July 2006**

Abstract. *We have constructed a near-infrared (NIR) spectroscopic sensing system on an experimental basis. The NIR system can be used for on-line real-time monitoring of milk quality items such as fat, protein, lactose, somatic cell count, and milk urea nitrogen during milking with sufficient*

The authors are solely responsible for the content of this technical presentation. The technical presentation does not necessarily reflect the official position of the American Society of Agricultural and Biological Engineers (ASABE), and its printing and distribution does not constitute an endorsement of views which may be expressed. Technical presentations are not subject to the formal peer review process by ASABE editorial committees; therefore, they are not to be presented as refereed publications. Citation of this work should state that it is from an ASABE meeting paper. EXAMPLE: Author's Last Name, Initials. 2006. Title of Presentation. ASABE Paper No. 06xxxx. St. Joseph, Mich.: ASABE. For information about securing permission to reprint or reproduce a technical presentation, please contact ASABE at rutter@asabe.org or 269-429-0300 (2950 Niles Road, St. Joseph, MI 49085-9659 USA).

precision and accuracy. However, when the calibration models developed from a data set were validated using a different data set, the performance of the calibration models was poor except for fat content. It seemed that various factors such as cow individuality, lactation stage and calving time caused the poor performance. However, it was not known which factor affected milk spectra and which wavelength range of the spectra was affected by the factors. We therefore analyzed milk spectra by principal component analysis in order to determine the reasons for poor performance. It was found that milk spectra were greatly affected by fat content and calving time. Calving time had a particularly great effect on the spectra in the wavelength range of 860 to 880 nm. In summary, using principal component analysis, we found the factor most affecting milk spectra and the wavelength of the spectra affected by the factor.

Keywords. fat content, calving time, loading, score plot

Introduction

Near-infrared spectroscopy (NIRS) is a new nondestructive method for obtaining qualitative information on foods and agricultural commodities. NIRS has already been put to practical use in automatic rice-quality inspection systems in Japan (Kawamura et al., 2002; Kawamura et al., 2003a). NIRS has also been used to assess milk quality (Sato et al., 1987; Tsenkova et al., 1999; Tsenkova 2001a; Tsenkova et al., 2001b; Tsenkova et al., 2001c; Natsuga et al., 2002), but it has been difficult to apply NIRS to real-time on-line monitoring of milk quality of individual cows during milking.

We have constructed an on-line near-infrared (NIR) spectroscopic sensing system on an experimental basis to assess milk quality, and we (Kawamura et al., 2003b) have reported that the NIR sensing system can be used for real-time assessment of milk quality during milking with sufficient precision and accuracy. We (Kawasaki et al., 2005) have also reported that the performance of the calibration models was poor except for fat when the calibration models developed from a data set were validated using a different data set. It seemed that various factors such as cow individuality, lactation stage and calving time caused the poor performance. However, it was not known which factor affected milk spectra and which wavelength range of the spectra was affected. The aim of this study was to determine the reasons for poor performance by analyzing milk spectra using principal component analysis (PCA).

PCA is an effective method of multivariate analysis for revealing variations between spectra. The objective of PCA is to describe the data by assessing a small number of variables which linear combination of the original variables. These synthetic variables are called principal components (PCs). Initially calculated PCs include more information on spectral variances than do later PCs. The main information that the spectral data hold is in the first PC (PC1) and the second PC (PC2). The characteristic of a PC is indicated by the loading. The PC and the loading are linked by

$$PC = \sum_{k=1}^n l_k a_k ,$$

where l_k is the loading of the k nm wavelength, n is the number of wavelength points, and a_k is the absorbance of the k nm wavelength. Analyses of PCs provide the main information on spectral data. Analyses of loadings provide the useful wavelength range of spectra that contribute to the information of PCs (Robert et al., 1996; Tanaka et al., 1995).

Near-infrared spectroscopic sensing systems

An on-line near-infrared (NIR) spectroscopic sensing system for assessing milk quality of individual cows during milking was constructed on an experimental basis. The system consists of an NIR instrument, a milk flow meter, a milk sampler and a laptop computer (Table 1). The system was attached between a teatcup cluster and a milk bucket of a milking machine. Raw milk from the teatcup cluster continuously flowed into the milk chamber of the spectrum sensor and flowed out through an outlet pipe for surplus milk to the milk flow meter. The optical axes of a halogen lamp and optical fiber were set to the same levels (Figure 1). The volume of milk sample in the chamber was about 230 mL. The spectrum sensor acquired diffusion transmittance spectra through the milk. The spectra were recorded in the range of 600 to 1050 nm at 1-nm intervals every 10 seconds during milking. Six continuous spectra were averaged to obtain a spectrum for one minute. (Figure 2)

Table 1. Specifications of the near-infrared spectroscopic instrument constructed on an experimental basis.

Devices	Specifications
Spectrum sensor	Diffusion transmittance spectrum sensor
Light source	Halogen lamp
Optical fiber	Silica glass fiber, 0.6 mm
Milk chamber surface	Glass
Volume of milk sample	Approx 230 mL
Distance between optical axis and milk level	93 mm
Spectrometer	Diffraction grating spectrometer
Optical density	Transmittance
Wavelength range	600 - 1050 nm, 1-nm intervals
Wavelength resolution	Approx 5 nm
Photocell	Linear array CCD, 2048 pixels
Thermocontroller	Peltier cooling system
Data processing computer	DELL, Windows XP, Celeron 1.06GHz, RAM 384KB
A/D converter	12 bit
Spectrum data acquisition	Every 10 seconds




Figure 1. Plane view of the near-infrared spectrum sensor constructed on an experimental basis.




Figure 2. Flow chart of an on-line near-infrared spectroscopic sensing system for assessing milk quality.

Cows and milk samples

Two Holstein cows belonging to Hokkaido University were used in this experiment (Table 2). These cows had calved during the experimental period. Milk samples were collected from the milk sampler every minute during milking. The milk constituents were determined using a Milkoscan 4000 (Foss Electric, Hillerod, Denmark).

Spectral data analyses

Transmittance spectra were transferred to absorbance spectra. Pretreatments of the spectra such as second derivative (Savitzky-Golay derivatives, number of smoothing points: 51) and multiplicative scatter correction (MSC) were performed. The Unscrambler ver.6.11 (Camo AS, Trondheim, Norway) was used for PCA with cross-validation.

Two PCs (PC1 and PC2) were calculated for raw milk spectra from milking of each cow. Two PCs were used to develop a score plot (PC1 on the x-axis and PC2 on the y-axis). The score plot provides graphical comparisons of the samples by taking into account the main information extracted from the spectra.

Table 2. Cows used in the experiment.

Cow number	Calving time	Date of calving	Experimental period	Number of reference samples
1116	2	16 Oct. 01	23 Oct. 01 - 12 Jun. 02	58
	3	19 Nov. 02	19 Nov. 02 - 25 Sep. 03	105
1110	2	20 Sep. 00	22 May. 01 - 18 Jul. 01	41
	3	25 Nov. 01	6 Nov. 01 - 22 May. 02	54

Results and discussion

Near-infrared spectra

Figure 3 shows an example of two sets of absorbance spectra (raw NIR and their pretreated spectra) of raw milk from a cow. In the pretreated spectra, the large negative peak in the spectra at the wavelength of 970 nm indicates second-overtone absorption by O-H strings. Two negative peaks in the spectra at the wavelengths of 740 nm and 840 nm indicate overtone absorptions by C-H strings and C-C strings.

Principal component analysis

Figures 4, 5, 6 and 7 show score plots for raw milk spectra of each cow. The total variances of the two PCs of cow 1116 and cow 1110 were 83.7% and 84.4%, respectively. When the score plots were classified into three levels of fat content shows in Table 3 (low fat content: ×, medium fat content: ■, high fat content: ◇), the score plots were separated into three groups along the x-axis (PC1) (Figures 4, 5). PC1 has the main information of the spectra, and scores were separated into groups according to fat content. Therefore, milk spectra were greatly affected by fat content. We (Kawasaki et al., 2005) have reported that the performance of the calibration model for determining fat content is good even if the model is affected by changes in various factors such as cow individuality, lactation stage and calving time. The reason for the

robustness of the calibration model for determining fat content was that milk spectra had much information on fat content.

When the scores were classified on the basis of difference in calving time (second calving time: ●, third calving time: ○), the score plots were separated into two groups along the y-axis (PC2) (Figures 6, 7). PC2 has the main information of the spectral data next to PC1, and scores were separated into groups according to calving time. Therefore, milk spectra were greatly affected by calving time. We (Kawasaki et al., 2005) have reported that the difference in calving time causes the poor performance of the calibration model. The reason for the poor performance was that milk spectra were affected by the difference in calving time.

Figures 8 and 9 show the loadings of PC1 and PC2 and the average spectrum of each calving time of each cow's datasets. In the case of PC1, peaks of the loading appeared at 740 and 840 nm. The wavelengths were the same as those of the negative peak of the spectra. Therefore, the peaks (740 and 840 nm) were associated with fat (triacylglycerol).

In the case of PC2, the prominent peak of the loading appeared in the wavelength range between 860 and 880 nm. Compared with the spectra of each calving time, the spectra differed widely in the same wavelength range. Therefore, the spectra of the wavelength range were affected by the difference of calving time. The spectra of the wavelength of 874 nm indicate overtone absorptions by C-C strings. When the calving time is changed, mammary gland cells are renewed. The size of fat globules changes with calving, and nutritional conditions also change with calving. The composition of unsaturated fatty acid is changed by change in nutritional conditions. Therefore, there is a possibility that the spectra wavelength was affected by changes in the composition of fatty acid and size of fat globules. However, we could not clarify which milk constituent with C-C strings was affected by the difference in calving time.




Figure 3. (a) Raw NIR spectra and (b) their pretreated spectra.

Table 3. Range of fat contents on score plots (Figures 4 and 5).

Fat range (%)	cow 1110	cow 1116
Low fat content	0.85 - 4.28	0.83 - 3.75
Medium fat content	4.33 - 5.40	3.79 - 5.31
High fat content	5.41 - 8.33	5.35 - 8.20




Figure 4. Score plot of PC1 and PC2 for raw milk spectra of cow 1116.
(Low fat content: x, Medium fat content: ■, High fat content: ◇)




Figure 5. Score plot of PC1 and PC2 for raw milk spectra of cow 1110.
(Low fat content: x, Medium fat content: ■, High fat content: ◇)




Figure 6. Score plot of PC1 and PC2 for raw milk spectra of cow 1116.
(second calving time: ●, third calving time: ○)




Figure 7. Score plot of PC1 and PC2 for raw milk spectra of cow 1110.
(second calving time: ●, third calving time: ○)




Figure 8. Loadings of PC1 and PC2
and the average spectrum of each calving time of cow 1116.




Figure 9. Loading of PC1 and PC2
and the average spectrum of each calving time of cow 1110.

Conclusion

We analyzed milk spectra by principal component analysis in order to determine the reasons for poor performance of calibration models. It was found that milk spectra were greatly affected by fat content and calving time. Calving time had a particularly great effect on the spectra in the wavelength range between 860 and 880 nm. Using principal component analysis, we found the factors most affecting milk spectra and the wavelength of the milk spectra affected by the factors.

References

- Kawamura. S., K. Takekura, and K. Itoh. 2002. Accuracy of Near-infrared Transmission Spectroscopy for Determining Rice Constituent Contents and Improvement in the Accuracy. ASAE Paper No. 023006. St. Joseph, Mich.: ASAE.
- Kawamura, S., M. Natsuga, K. Takekura, and K. Itoh. 2003a. Development of an automatic rice-quality inspection system. *Computers and Electronics in Agriculture*. 40, 115-126. Elsevier Science.
- Kawamura. S., M. Tsukahara, M. Natsuga, and K. Itoh. 2003b. On-line Near-Infrared Spectroscopic Sensing Technique for Assessing Milk Quality during Milking. ASAE Paper No. 033026. St. Joseph, Mich.: ASAE.
- Kawasaki. M., S. Kawamura, H. Nakatsuji and M. Natsuga. 2005. Online Real-time Monitoring of Milk Quality during Milking by Near-infrared Spectroscopy, ASAE Paper No. 053045. Tampa, Florida: ASAE.
- Natsuga. M., S. Kawamura, and K. Itoh. 2002. Effects of Wavelength Range and Light Path-length on the Accuracy of the Constituent Analysis of Unhomogenized Milk Using Near-infrared Spectroscopy. *J of Jpn Soc of Agricultural Machinery*. 64(5): 83-88.
- Robert. P., M.-F. Devaux and D. Bertrand. 1996. Beyond prediction: extracting relevant information from near infrared spectra, *J. Near infrared Spectros.* 4:75-84.
- Sato. T., M. Yoshino et al. 1987. Analysis of Milk Constituents by the Near-infrared Spectrophotometric Method. *Jpn. J. of Zootechnical Science*. 58(8): 698-706.
- Shenk, J.S. and M.O. Westerhaus. 1993. Analysis of agriculture and food products by near-infrared reflectance spectroscopy. 13-16. Port Matilda, PA: Infrasoft International Co.
- Tanaka. M., A. Shibata, N. Hayashi, T.Kojima, H. Maeda, Y. Ozaki. 1995. Discrimination of commercial natural mineral waters using near infrared spectroscopy and principal component analysis, *J. Near infrared Spectros.*3:203-210.
- Tsenkova. R., S. Atanassova, K. Toyoda, Y. Ozaki, K. Itoh, and T. Fearn. 1999. Near-infrared Spectroscopy for Dairy Management: Measurement of Unhomogenized Milk Composition. *J Dairy Sci*. 82: 2344-2351.
- Tsenkova. R. 2001a. Near-infrared Spectroscopy for Dairy Precision Farming. ASAE Paper No. 013009. St. Joseph, Mich.: ASAE.
- Tsenkova. R., S. Atanassova, S. Kawano, and K. Toyoda. 2001b. Somatic cell count determination in cow's milk by near-infrared spectroscopy: A new diagnostic tool. *J Anim Sci* 79: 2550-2557.
- Tsenkova. R., S. Atanassova, and K. Toyoda. 2001c. Near-infrared Spectroscopy for Diagnosis: Influence of Mammary Gland Inflammation on Cow's Milk Composition Measurement.